

**ELATION® CUEPIX BLINDER WW4™**  
**DMX Channel Values / Functions (9 DMX Channels)**

Specifications are subject to change without any prior written notice.

*\*Control of (4) COB Modules chase direction depends on the Flip setting.*

MODE / CHANNEL						VALUE	FUNCTION
1 CH	2 CH	4 CH	5 CH	7 CH	9 CH		
1	1						ALL (4) COB MODULES
						0-255	Intensity 0 to 100%
		1	1	1	1		*COB #1 MODULE DIMMER
						0-255	Intensity 0 to 100%
		2	2	2	2		*COB #2 MODULE DIMMER
						0-255	Intensity 0 to 100%
		3	3	3	3		*COB #3 MODULE DIMMER
						0-255	Intensity 0 to 100%
		4	4	4	4		*COB #4 MODULE DIMMER
						0-255	Intensity 0 to 100%
					5		INTERNAL MACROS
						0-20	Normal
						21-42	DREAM
						43-64	METEOR
						65-87	FADE
						88-110	CHANGE
						111-123	FLOW 1
						124-146	FLOW 2
						147-169	FLOW 3
						170-192	FLOW 4
						193-255	NO Function
					6		MACRO SPEED
						0-255	MACRO Program Speed SLOW to FAST
	2		5	5	7		MASTER DIMMER
						0-255	Intensity 0 to 100%
				6	8		FLASH / STROBE
						0-31	COB OFF
						32-63	COB ON
						64-95	FLASH Strobe Effect SLOW to FAST
						96-127	COB ON
						128-159	PULSE Strobe Effect SLOW to FAST
						160-191	COB ON
						192-223	RANDOM Strobe SLOW to FAST
						224-255	COB ON
				7	9		DIMMING CURVE MODES
						0-20	STANDARD
						21-40	STAGE
						41-60	TV
						61-80	ARCHITECTURAL
						81-100	THEATRE
101-255	Default to Unit Setting						

**ELATION** | CUEPIX BLINDER WW4™ | dmx traits

**Elation Professional USA** | 6122 S. Eastern Ave. | Los Angeles, CA. 90040

323-582-3322 | 323-832-9142 fax | [www.elationlighting.com](http://www.elationlighting.com) | [info@elationlighting.com](mailto:info@elationlighting.com)

**Elation Professional B.V.** | Junostraat 2 | 6468 EW Kerkrade, Netherlands

+31 45 546 85 66 | +31 45 546 85 96 fax | [www.elationlighting.eu](http://www.elationlighting.eu) | [info@elationlighting.eu](mailto:info@elationlighting.eu)